

Product information

AC 162150

Adhesive primer metal

This magazine has an advisory function. However, the user must test the application of this product against the circumstances and possibilities that apply to him. No liability or guarantee can be derived from the text of this sheet. You can always consult us for information.



Delta 32, 6825 MS Arnhem
T +31 (0) 26 388 21 02
F +31 (0) 26 364 41 51
Email: info@plantag.nl
Website: www.plantag.nl

Product

1K Adhesive primer AC 162150 for metal. Available in: white AC 262150.3 and transparent AC 162150.1.

Product description

1K Adhesive primer for metal AC 162150, based on phenol resins and polyvinyl butyral.

Field of application

Fast drying 1K adhesive primer for various metals such as steel, aluminum and zinc, to ensure bonding. Before use clean surface and test adhesion on surface.

Technical data

Gloss	Does not applicable
Color	Transparent and white
Gloss	Does not applicable
Mixing ratio	Does not applicable
Thinner	SO 662263
Delivery viscosity	Ca. 25-40 sec.
Spray viscosity	Ca. 25-40 sec.
Potlife	Does not applicable
Solid contents	Ca. 19 %
Storage stability	In original unopened packaging 12 months in a cool, dry and frost-free place



Adhesive primer metal

This magazine has an advisory function. However, the user must test the application of this product against the circumstances and possibilities that apply to him. No liability or guarantee can be derived from the text of this sheet. You can always consult us for information.

Delta 32, 6825 MS Arnhem
T +31 (0) 26 388 21 02
F +31 (0) 26 364 41 51
Email: info@plantag.nl
Website: www.plantag.nl

Application

Application method	Spray
Layers	1 layer
Yield per layer	70-100 gr/ m ²
Max. Yield	120 gr/ m ²
Optimal temp. working space	16-18 °C
Optimal humidity	60 %
Material temperature	16-20 °C
Cleaning Thinner	SO 602020
Pre-treatment	Decrease, Clean well
Suitable on bleached wood	Does not applicable
UV resistance	Does not applicable
Optimal moisture content wood	Does not applicable.
Drying times	20 min. dust dry at 20 °C. 180 min. sprayable. Forced drying will reduce the drying time.

Disposal

Treat waste from paints or oil as chemical waste dispose of as chemical waste.

Package

Available in 10 Kg cans.

Safety, Standards and Durability

UN Code 1263, paint, 3, VG II, (D/E) , GGVS / ADR
Info Safety data sheet.

